

SP Climatic Chambers

SP 260 BVEHF



Maintain Homogeneous Environmental Conditions

Supporting temperatures up to 60°C and relative humidity of 95%, Froilabo climatic chambers can be used to perform accelerated ageing, stability testing, drying, burn-in tests and much more.

PERFORMANCE


Temperature range	10°C to 60°C
Relative humidity range	10 to 95% RH

WARRANTY

Parts	2 years
-------	---------



Maximum temperature of 60 °C



Available in 3 volumes

Technical Specifications

SP CLIMATIC CHAMBERS	
MODEL	SP 260 BVEHF
GENERAL SPECIFICATIONS	
Volume (net)	330 liters
External Dimensions (H x W x D)	1770 x 960 x 670 mm
Internal Dimensions (H x W x D)	1000 x 600 x 550 mm
External Construction	Made of epoxy painted electrogalvanized sheet steel
Internal Construction	Stainless steel
Weight (net)	185 Kg
Standard equipment	Full door Demineralized water supply by 10 liter tank Wall passage diameter 35 mm 4 wheels including 2 self-locking
Shelves (575 X 475 mm)	2 anti-tipping stainless steel wire shelves as standard (max weight / shelf: 20 kg)
Working Temperature	10°C to 60°C
Environment	Not designed for use in an explosive atmosphere (ATEX)
Guarantee	2 years
ENVIRONMENTAL CONTROLS	
Heating system	Heating by convection provided by a fan (neither conduction nor radiation)
Refrigeration system	Refrigeration provided by a hermetic compressor air condenser
Refrigerant charge	CFC-free and non-flammable refrigerant R452A
Moisture production	Ultrasonic water vapor generator (rapid rise in humidity after door opening)
Nebulizer life	10,000 hours
ELECTRICAL AND ELECTRONIC DATA	
Controller type	Double electronic regulation by self-regulating PID. Real digital display and setpoint (at 1/10° for temperature)
Temperature probe	Temperature measurement by PT100 Ohms probe
humidity sensor	Relative humidity measurement by capacitive sensor
List of alarms	Class 3.1 independent overtemperature thermostat. Visual alarm - high security
Types of alarms	Visual
Energy Consumption	1 600 watts
Types of power supply	230 V single phase + T - 50 Hz
PERFORMANCE (AMBIENT TEMPERATURE: 22°C)*	
Temperature range	10°C to 60°C
Adjustable humidity	From 10 to 95% RH depending on the associated temperature
Long term stability	+25°C / 60% HR. +30°C/ 65% HR
Accelerated aging	+40°C / 75% HR
Intermediate condition	+30°C / 60% HR
TESTS FOR SEMI-PERMEABLE:	
Long term stability	+25°C / 40% HR
Accelerated aging	+40°C / 25% HR
OPTIONS & COMPLIANCE	
Options	<ul style="list-style-type: none"> Key lock 16-segment T°C and RH programmer Different sound alarms
Supplied with	<ul style="list-style-type: none"> 2 shelves Demineralized water supply by 10 liter tank 35 mm diameter wall passage with plug on the right side Mounted on casters, 2 of which are self-locking Humidity trap for HR Z3 range extension (see climatogram)
Certification / Conformities	Equipment compliant with CE regulations
Shipping weight	200 Kg
Shipping Dimensions (H x W x D)	1950 x 1210 x 800 mm

* Measured according to AFNOR NFX 15-140 standard. Homogeneity required for the following temperature / humidity pairs: +/-2°C & +/-5% RH stipulated in the ICH Guideline Q1A standard.