

Thermostatic Water Bath

BMP 30



Specially designed for serology

Ideal for modern laboratories, our serological bath is available in 2 volumes; 3 and 6 litres, and consists of a transparent plexiglass and a control interface via a button. This makes it very easy to use and set the ambient temperature between 7°C to 60°C.

PERFORMANCE


Ambient temperature range	7°C to 60°C
Factory preset	37°C and 56°C
Capacity	3L

WARRANTY

Parts	2 years
-------	---------



Water lack
safety



Available in
2 volumes

Technical Specifications

SEROLOGIC WATER BATH	
MODEL	BMP 30
GENERAL SPECIFICATIONS	
Capacity (net)	3 litres
Temperature Range (ambient)	7°C to 60°C
Construction	Polycarbonate frame
External Dimensions (W x H x D)	360 x 120 x 130 mm
Internal Dimensions (W x H x D)	280 x 110 x 80 mm
Weight (gross)	3kg
Weight (net)	1.5kg
Factory Setpoint	37°C and 56°C
Water lack safety	Yes
Warranty	2 years
ELECTRICAL DATA	
Power supply	230V ~ +/-10%, 50 Hz
Energy consumption	250 W
COMPLIANCE	
Device complies with CE specifications	
OPTIONS	
Polycarbonate lid	
1 rack for 60 tubes diam. 14mm	
Thermometer	

* Cleaning and decontamination with detergents and antimicrobials used in hospitals (Ammonium quaternary / except pure bleach)