

# DATA SHEET

## BIO EXPERT | 240 L



Reference	
BE240	
General specifications	
Net volume	223 liters
Dimensions : externals (H x W x D) internals (H x W x D)	1230 x 626 x 679.5 mm / 48.4 x 24.7 x 26.8 in. 980 x 500 x 456 mm / 38.6 x 19.7 x 18.0 in.
Construction : external internal	Electrogalvanised steel with epoxy paint Brushed stainless steel inner tank
Net weight	82 kg / 180.8 lb
Standard construction	A fully closed door, easy closure « hands free » Safety glass inner door 4 levelling feet 2 cables entry port (30mm) - left side 1 power cord (1.5m)
Shelves (W x D : 480 x 430 mm / 18.9 x 16.9 in.)	2 anti-tilt stainless steel wire shelves as standard (max weight / shelf: 20 kg) Maximum numbers of shelves : 18 (max total weight : 90kg)
Working temperature	From +18°C to +32°C
Indoor / outdoor use	For indoor use only
Environment	Not designed for use in explosive atmospheres (non EX-proof)
Warranty	2 years
Heating system	
Heating system	Heating convection ensured by fan (no risk of conduction or radiation)
Ventilation method	Turbine ventilation ensuring temperature homogeneity
Air renewal	Adjustable on the front, rear exhaust
Electric and electronic data	
Controller type	Electronic PID self regulating and self-adaptive Programmable controller
Temperature probe	1 x Pt100 3 wires probe
List of alarms	<ul style="list-style-type: none"> <li>High temperature</li> <li>Overtemperature safety class II according to the European standard EN 61010-2-010 (DIN 3.1 equivalent)</li> </ul>
Types of alarms	Visual
Energy consumption	1500 W
Types of power supply	<ul style="list-style-type: none"> <li>Voltage 230V ~ +/-10%, 50 Hz</li> <li>Voltage 110V ~ +/-10%, 50/60Hz</li> <li>Voltage 220V ~ +/-10%, 60Hz</li> </ul>
Performances (ambient temperature : 22°C)	
Temperature range	Amb +5°C to 100°C, 1/10th degree display (set and actual temperature)
Temporal stability	+/-0.1°C
Homogeneity at 37°C	+/-0.5°C

Sterilisation	
Type of sterilisation	Thermal disinfection by dry heat at 160°C for 2h30 Operating indicator by LED
Starting method	Starting and protection of the cycle by a key switch
Options and conformities	
Options	<ul style="list-style-type: none"> <li>• Chart recorder</li> <li>• Key door lock</li> <li>• Characterization 9 points according to EN60068-3-11</li> <li>• Stainless Steel Perforated shelf</li> <li>• Lowenstein trays</li> <li>• 4 castors</li> <li>• Basement with or without castors</li> <li>• Additional cable entry port</li> </ul>
Supplied with	<ul style="list-style-type: none"> <li>• 2 Shelves</li> <li>• 1 power cord</li> <li>• User manual</li> </ul>
Certification / Conformities	<ul style="list-style-type: none"> <li>• Equipment meets the specifications and CE compliant to EN60068-3-11</li> <li>• 2014/35/UE – Low voltage directive</li> <li>• 2014/30/UE – EMC directive, Class A device</li> <li>• 97/23/CE – Under pressure devices</li> </ul>
Shipping	
Shipping dimensions (H x W x D)	1400 x 750 x 670 mm / 55.1 x 29.5 x 26.4 in
Shipping weight	96 kg / 211.7 lb

©2019 Froilabo. All rights reserved.

FROILABO products are designed in France and made in E.U on a ISO9001 site.  
The specifications and technical data presented in this datasheet are those in our possession on the date of emission. FROILABO reserves the right to make, without notice, any modifications to its products, specifications, colors, materials and technical data, or to interrupt the manufacture of the products.  
Despite the care taken in its realization, this product sheet does not constitute a contractual document.

For more informations, go to sur [www.froilabo.com](http://www.froilabo.com).  
FP\_BE240/EN\_rev1.0 | 08/2019

Headquarter address : Froilabo, 5 avenue Lionel Terray 69330 Meyzieu, France