

DATA SHEET

COOLSTORE | 600 L | -0°C



Reference	
COOLS600	
General specifications	
Net volume	600 liters
Dimensions : externals (H x W x D)	2130 x 700 x 910 mm
internals (H x W x D)	1550 x 530 x 660 mm
Construction : external /internal	Stainless steel AISI304
Net weight	170 kg
Standard construction	1 full door 4 casters (2 with breaks) Ø 35mm cable entry port (right side) Enclosure keylock 1 power cord (1.5m)
Shelves (W x D : 530 x 655 mm)	4 shelves as standard (max weight / shelf: 50 kg)
Ambient temperature	From +18°C to +32°C
Indoor / outdoor use	For indoor use only
Environment	Not designed for use in explosive atmospheres (non EX-proof)
Warranty	2 years
Refrigeration and heating system	
Heating technology	Heat resistance
Cooling engine	Hermetic compressor with ventilated compressor and interchangeable filter
Refrigerante load	R134a (CFC & HCFC free)
Ventilation system	Forced air circulation ensuring homogeneity
Electric and electronic data	
Controller type	Electronic PID self-regulating
Temperature probe	1 x Pt100
Alarms	High and low temperature Independant overtemperature safety thermostat (3.1 grade)
Types of alarms	Visual
Power consumption	1650 W
Types of power supply	Voltage 230V ~ +/-10%, 50 Hz
Performances (ambient temperature : 22°C) AFNOR NFX 15-140	
Temperature range	From -0°C to to 60°C, 1/10th degree display (set and actual temperature)
Temporal stability	+/-0.2°C
Homogeneity	+/-1°C

Options and conformities

Options	<ul style="list-style-type: none">• Additional ø 50mm cable entry port• Additional shelf (1 shelf for 600L / 2 shelves for 1300L)• cable entry port• Automatic defrost (recommanded for 0 to +10°C continuous use)• Temperature recorder• IQ/OQ/PQ files• 3 levels programmable lighting• COFRAC factory temperature mapping (1 product / 1 setpoint)• Pt 100 Ohms + DIN plug for external recorder• Installation & commissioning by Froilabo• Previous device disposal (excluding any handling costs)• Special delivery by team of handler
Supplied with	<ul style="list-style-type: none">• User manual
Certification	<ul style="list-style-type: none">• Equipment complies with CE regulations

Shipping

Shipping dimensions (H x W x D)	2280 x 940 x 1040 mm
Shipping weight	190 kg



Also available in 1300L

©2020 Froilabo. All rights reserved.

FROILABO products are designed in France and produced in E.U.
The specifications and technical data presented in this datasheet are those in our possession on the date of emission. FROILABO reserves the right to make, without notice, any modifications to its products, specifications, colors, materials and technical data, or to interrupt the manufacture of the products.
Despite the care taken in its realization, this product sheet does not constitute a contractual document.

For more informations, go to sur www.froilabo.com.
FP_COOLS600_0_EN_rev1.0 | 03/2020

Headquarter address : Froilabo, 5 avenue Lionel Terray 69330 Meyzieu, France